



TP2103 21.5” TOUCHSCREEN

Robust, Flexible & Cost-Effective



The JACS **TP2103** touchscreen delivers a robust, flexible, and cost-effective platform for user engagement. The TP2103 is built to withstand heavy use and its form factor is perfect for mounting in tamper-resistant enclosures, making it an ideal platform solution for wayfinding, digital directories, secure self-checkout, and interactive kiosks.

Customization Benefits

Empower your workforce with value-generating solutions designed specifically to meet the needs of your business.



Hardware

- Long product life cycle
- Seamless infrastructure integration
- Certified and Compliant



Firmware

- Highly secure
- Easy deployment
- Controlled user experience



Connectivity

- Ethernet
- Wi-Fi
- Bluetooth

TP2103 TOUCHSCREEN SPECIFICATIONS

CPU RK3288W Quad-Core Cortex A17, Up to 1.6GHz	BLUETOOTH Version 5.0
RAM/ROM 2GB DDR3 / 16GB (4GB / 32GB Optional)	AUDIO 3.5mm CTIA earphone jack, Internal Microphone, Dual Speakers (4ohms/3W)
OPERATING SYSTEM Android 8.1	PORTS/SLOTS HDMI Type A (Output) x 1; Micro USB x 1 (Host / Slave); USB Host 2.0 x 2; Micro SD Card Slot x 1 (up to 128 GB)
RESOLUTION 1920 x 1080 pixels	INPUT POWER DCIN Power: 12V/3A with Over Voltage Protector; 60W Ultra PoE(PoE++) Switch; 60W Passive PoE Injector (Output:42V-57V)
SCREEN SIZE 21.5 inches	SENSORS Gravity Acceleration Sensor (G-Sensor)
SCREEN SPECIFICATIONS Brightness up to 250 nits, 10-point Capacitive Touch Panel	OPERATING TEMPERATURE 32° F to 122° F
CAMERA Front: 5MP Auto-Focus	WEIGHT 10.8 lbs
ETHERNET RJ45 10/100/1000 Mbps Auto	DIMENSIONS 20.90" x 12.68" x 2.00"
WLAN Wi-Fi IEEE 802.11a/b/g/n/ac Dual-band 2.4GHz/5GHz	MOUNTING INTERFACE VESA 75mm x 75mm / 2.95" x 2.95" VESA 100mm x 100mm / 3.94" x 3.94"