

TD0551 INDOOR CBRS CPE

Flexible, Reliable & Secure







The JACS **TD0551** Indoor CBRS CPE empowers enterprise businesses to take full advantage of the coverage and capacity benefits of their LTE networks. The TD0551 is designed with speed and connectivity in mind and offers features like dual band Wi-Fi, Voice Over LTE, and advanced network security and admin protocols.

Customization Benefits

Empower your workforce with value-generating solutions designed specifically to meet the needs of your business.



- ·Long product life cycle
- · Seamless infrastructure integration
- · Certified and Compliant



Firmware

- · Highly secure
- $\cdot \mathsf{Easy} \ \mathsf{deployment}$
- · Controlled user experience



Connectivity

- · Private LTE
- ·Wi-Fi

TD0551 INDOOR CBRS CPE SPECIFICATIONS

CHIPSET Qualcomm SDX12+RTL8197FH	RAM/ROM 1 GB/2GB
CELLULAR BANDS AND THROUGHPUT LTE CAT 12 Band 42/43/48 LTE DL 450Mbps/UL 30Mbps 4x4 MIMO	WLAN 2.4G/5GHz Dual Band 802.11 a/b/g/n/ac 2 x 2 MIMO
SIM 4FF, Nano-SIM	INTERFACES 4 x RJ45 (1 x GE LAN/WAN, 3 x GE LAN) 1 x power adapter port 1 x Reset Hole 1 x Micro USB 2.0 (For Debug Only)
LED LIGHTS 5 LED Indicators (PWR, INTERNET, Wi-Fi/WPS, WAN/LAN, RF Signal)	BUTTONS WPS button / Power button
ENVIRONMENT Operation Temperature: -10 to 55°C Operation Humidity: 10% to 80% Storage Temperature: -40 to 85°C Storage Humidity: 5% to 95%	ADDITIONAL FEATURES Support Up To 64 Wi-Fi User connections
WEIGHT 235g / 0.52lbs	DIMENSIONS 179 × 36 × 128 mm / 7.05 x 1.42 x 5.04 in
PACKING LIST 1 x Assembled product 1 x 12V/1A DC Adapter	

