



JACS LTE DONGLE 400

Fast, Mobile & Reliable



The **JACS LTE Dongle 400** offers a compact design with ultrasonic plastic welding for portability, IP66 protection, extensive LTE band support and adaptive thermal management for improved performance. It also features easy plug-and-play setup without the need for additional drivers or software installation.

Customization Benefits

Empower your workforce with value-generating solutions designed specifically to meet the needs of your business.



Hardware

- Long product life cycle
- Seamless infrastructure integration
- Certified and Compliant



Firmware

- Highly secure
- Easy deployment
- Controlled user experience



Connectivity

- Cellular

JACS LTE DONGLE 400 SPECIFICATIONS

| | |
|---|---|
| CHIPSET Qualcomm MDM9x07 | MEMORY (SDRAM/NAND) 128MB/256MB |
| THROUGHPUT LTE CAT 4 FDD-LTE 150Mbps/50Mbps | USB USB power supply 5V/1A Type-C Male, USB 2.0 |
| OPERATING SYSTEM Windows: 7/8/10/XP/Vista MAC OS: 10.7+ Linux: Ubuntu 13.04+, Android Browser: IE9+, Firefox, Google Chrome, Safari, Opera | SIM 4FF SIM card 3V SIM card and 1.8V SIM card |
| CELLULAR NETWORK UMTS: B1/2/4/5/8 LTE FDD: B1/2/3/4/5/7/8/12/17/20 | ANTENNA Internal Antenna |
| OPERATING TEMPERATURE -4°F to 140°F | INDUSTRIAL PROTECTION IP66 ESD Protection Circuit Contact ± 8KV Air ± 15KV |
| STORAGE TEMPERATURE -40°F to 158°F | DIMENSIONS 2.48" x 0.87" x 0.52" |